

NAVI-LED for the emotional moments of life



G.L.E. Gesellschaft für lichttechnische Erzeugnisse mbH

Member of NARVA e.V. Germany 

NAVI - LED

SOLID GLASS - NO PLASTIC

the revival of the standard light bulb

Solid glass construction

Up to 80% less energy

compared to incandescent lamps

360 light angle




The perfect LED Retrofit light bulb

- Up to **80%** energy saving compared to incandescent lamps
- Perfect fit into existing application
 - 360 light angle
 - Plug and Play solution
- Robust construction
 - Solid glass construction (NO plastic)



Solide glass
NO plastic



NLED-F



NLED-FC

Name	Product group	Type	Wattage	Voltage	Frequency	light angle/ke	Operation Temp	Base	Lumen	Dimmable	Life time	Color Rendering	Color Temperature	Schutzklasse	Glass	Equivalent	Energy Class
NLED-FCC 3W 220V 830 E14 noDi	NAVI-LED	Filament	3	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	300	no	30.000 h	>80	2800	IP 20	clear	35W	A++
NLED-FCF 3W 220V 830 E14 noDi	NAVI-LED	Filament	3	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	300	no	30.000 h	>80	2800	IP 20	frosted	35W	A++
NLED-FCC 1,8W 220V 830 E14 noDi	NAVI-LED	Filament	1,8	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	200	no	30.000 h	>80	2800	IP 20	clear	20W	A++
NLED-FCF 1,8W 220V 830 E14 noDi	NAVI-LED	Filament	1,8	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	200	no	30.000 h	>80	2800	IP 20	frosted	20W	A++
NLED-FCC 3,5W 220V 830 E14 noDi	NAVI-LED	Filament	3,5	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	400	no	30.000 h	>80	2800	IP 20	clear	40W	A++
NLED-FCF 3,5W 220V 830 E14 noDi	NAVI-LED	Filament	3,5	220 - 240 V	50/60 Hz	360	-20 to +50 C	E14	400	no	30.000 h	>80	2800	IP 20	frosted	40W	A++
NLED-FC 4W 220V 830 E27 noDi	NAVI-LED	Filament	4	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	480	no	30.000 h	>80	2800	IP 20	clear	40W	A++
NLED-FF 4W 220V 830 E27 noDi	NAVI-LED	Filament	4	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	480	no	30.000 h	>80	2800	IP 20	frosted	40W	A++
NLED-FC 5,5W 220V 830 E14 noDi	NAVI-LED	Filament	5,5	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	600	no	30.000 h	>80	2800	IP 20	clear	60W	A++
NLED-FF 5,5W 220V 830 E14 noDi	NAVI-LED	Filament	5,5	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	600	no	30.000 h	>80	2800	IP 20	frosted	60W	A++
NLED-FC 7W 220V 830 E14 noDi	NAVI-LED	Filament	7	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	800	no	30.000 h	>80	2800	IP 20	clear	70W	A++
NLED-FF 7W 220V 830 E14 noDi	NAVI-LED	Filament	7	220 - 240 V	50/60 Hz	360	-20 to +50 C	E27	800	no	30.000 h	>80	2800	IP 20	frosted	70W	A++
NLED 5W 220V 830 GU10 noDi	NAVI-LED	LED	5	220 - 240 V	50 Hz	36	-20 to +50 C	GU10	250	no	25.000 h	80	2700		clear	35W	A



3W

5,5W


10W




30W

50W

100W



warm white → 830



neutral white → 865

Überreicht durch:

G.L.E. Gesellschaft für lichttechnische Erzeugnisse mbH

Herzbergstr. 26
10365 Berlin
Germany

Member of NARVA e.V. Germany

E-Mail: info@narva-gle.com
Internet: www.narva-gle.com